



## Mercedes-Benz Arocs 2543 LS 6x2 Tractor Unit

L-cab ClassicSpace, 2.30 m, tunnel 170 mm

410L Aluminium Fuel Tank

30L AdBlue Tank

Active Brake Assist 4

VDO electronic Tachograph

Proximity Control Assist

Lane Keeping Assist

Availability      In Stock

### Specifications

Make/Model: Mercedes-Benz Arocs 2543 LS 6x2

Engine Size & Output: Mercedes OM470 inline, 6 cylinder diesel engine, 10.7 litres output 428 hp. Euro 6 with OBD-C  
Power/Engine Torque @ 1100rpm 2100nm

Gearbox: Mercedes Power shift 3, 12 speeds with off road program.

Chassis Details: L-cab Classic Space, 2.30 m, tunnel 170 mm

Wheels & Tyres: Alcoa Durabrites 9 x 22.5  
1st Axle: 2x 315/70 R 22,5 Bridgestone F38L19 75 Highway  
2nd Axle: 2x 315/70 R 22,5 Bridgestone F38L19 75 Highway  
3rd Axle: 4x 315/70 R 22,5 Bridgestone F38L78 75 Traction (M+S)

Brake System: Disc Brake on Front and Rear Axles  
Parking Brake additional on First Axle  
Electronic braking system with ABS and ASR

---

Axles & Suspension: Front Axle 7.5 t Straight Version  
Front spring, 7.5 t, 2-leaf  
Leading axle, 7.5 t, de-loadable, liftable  
Rear axle, crown wheel 440, hypoid, 13.0 t  
Differential lock, rear axle

---

Cab Exterior: Finished in Arctic White  
Reverse Warning Combined With Hazard Warning Lights  
Fog Lamps  
LED Running Lamps  
Worklamp

---

Cab Interior: RH Drive  
Driver's suspension seat comfort  
Fold-up co-driver's seat  
Seat cover velour driver's seat  
Seat cover velour co-driver's seat centre seat  
Sunblind side driver's side  
Air conditioning system  
Stowage flaps above windscreen  
Roof hatch/vent roof  
Multifunction steering wheel  
Bottle holder  
Power windows all-round  
Entrance lamps in door panel  
Document stowage space, A4 size  
Additional socket 12 V/15 A co-driver footwell  
Socket 24 V/15 A co-driver footwell  
Instrument cluster 12.7 cm with video function  
VDO Tachograph digital EC rpm ADR  
CD radio Bluetooth

---

Additional Items: Driver's suspension seat, comfort  
Residual engine heat utilisation  
Auxiliary hot water heater, cab  
Drawers, under bed  
Socket, 24 V/15 A, behind seat  
PSM, body and trailer CAN, ISO 11992  
L-cab ClassicSpace, 2.30 m, tunnel 170 mm  
High Performance Engine Brake  
Water pump, governed  
PTO MB 131-2c, pump  
Transmission oil cooling  
Lowered frame, with residual bellow pressure ctrl

---