



Mercedes-Benz Arocs 2543 LS 6x2 Tractor Unit

L-cab ClassicSpace, 2.30 m, tunnel 170 mm

410L Aluminium Fuel Tank

30L AdBlue Tank

Active Brake Assist 4

VDO electronic Tachograph

Proximity Control Assist

Lane Keeping Assist

Availability In Stock

Specifications

Make/Model: Mercedes-Benz Arocs 2543 LS 6x2

Engine Size & Output: Mercedes OM470 inline, 6 cylinder diesel engine, 10.7 litres output 428 hp. Euro 6 with OBD-C
Power/Engine Torque @ 1100rpm 2100nm

Gearbox: Mercedes Power shift 3, 12 speeds with off road program.

Chassis Details: L-cab Classic Space, 2.30 m, tunnel 170 mm

Wheels & Tyres: Alcoa Durabrites 9 x 22.5
1st Axle: 2x 315/70 R 22,5 Bridgestone F38L19 75 Highway
2nd Axle: 2x 315/70 R 22,5 Bridgestone F38L19 75 Highway
3rd Axle: 4x 315/70 R 22,5 Bridgestone F38L78 75 Traction (M+S)

Brake System: Disc Brake on Front and Rear Axles
Parking Brake additional on First Axle
Electronic braking system with ABS and ASR

Axles & Suspension: Front Axle 7.5 t Straight Version
Front spring, 7.5 t, 2-leaf
Leading axle, 7.5 t, de-loadable, liftable
Rear axle, crown wheel 440, hypoid, 13.0 t
Differential lock, rear axle

Cab Exterior: Finished in Arctic White
Reverse Warning Combined With Hazard Warning Lights
Fog Lamps
LED Running Lamps
Worklamp

Cab Interior: RH Drive
Driver's suspension seat comfort
Fold-up co-driver's seat
Seat cover velour driver's seat
Seat cover velour co-driver's seat centre seat
Sunblind side driver's side
Air conditioning system
Stowage flaps above windscreen
Roof hatch/vent roof
Multifunction steering wheel
Bottle holder
Power windows all-round
Entrance lamps in door panel
Document stowage space, A4 size
Additional socket 12 V/15 A co-driver footwell
Socket 24 V/15 A co-driver footwell
Instrument cluster 12.7 cm with video function
VDO Tachograph digital EC rpm ADR
CD radio Bluetooth

Additional Items: Driver's suspension seat, comfort
Residual engine heat utilisation
Auxiliary hot water heater, cab
Drawers, under bed
Socket, 24 V/15 A, behind seat
PSM, body and trailer CAN, ISO 11992
L-cab ClassicSpace, 2.30 m, tunnel 170 mm
High Performance Engine Brake
Water pump, governed
PTO MB 131-2c, pump
Transmission oil cooling
Lowered frame, with residual bellow pressure ctrl
