



**HYVA
SKIP LOADER**

**DAF LF260 FA 4x2 HYVA
SKIP LOADER**

CHASSIS SPECIFICATION

Issued
OCTOBER 2022

DAF LF260 FA 4x2 HYVA SKIP LOADER

Make / Model:

DAF LF260 FA 4x2 19 Ton Construction Rigid Chassis

Driveline:

Drive line is fitted with a 6.7 litre, 6 cylinder diesel Euro PX-7 engine:

- Output: 194kW at 2300 rpm
- Max Torque: 1000 Nm at 1000 to 1700 rpm

Also features a MANUAL override 6 speed 6S1000 gearbox, mechanical differential lock, ASR (anti-slip control), and OBD (on-board diagnostics).

Cab External Features:

Green translucent external sun visor.

Galvanised steel bumper.

Tinted glass.

Electric operated side windows.

4 point mechanical cab suspension and integrated shock absorbers.

Central door locking system with exterior light checker functions.

Electrical adjustment of main mirror and wide angle mirror.

Daytime running lights with four LEDs at each side.

Single glassed window in cab rear wall

Colour:

Cab is finished in H3279WHITE. Lower cab step, cab steps, wings and bumper are finished in stone grey. Chassis finished in Grey.



CHASSIS SPECIFICATION

Issued
OCTOBER 2022

DAF LF260 FA 4x2 HYVA SKIP LOADER

Cab Interior:

Cab interior is finished with black rock and a dark sand trim. Driver seat is air suspended with high back and comfort air. Upholstery is flash copper with black seat belts. Air-Con can be manually controlled with air recirculation.

Cab also features a radio / USB player, truck phone, hands free telephone kit with SIM card slot, Bluetooth antenna and two USB charging points. There is also a 5" TFT display in the instrument panel and driver performance assistant (DPA). Stoneridge or VDO digital tachograph.

Chassis:

Chassis is 270 mm x 8 mm steel with a single low horizontal DPF & SCR exhaust system unit with vertical discharge behind cab. 200 L plastic fuel tank located N/S and 45 litre AdBlue tank on second front axle in driver's side. Wheel base is 3750 mm with 1120 mm overhang. Mudguards have spray suppression.

Braking System:

Features ventilated disc brakes on the front and rear axles and dual circuit air system with electronic control (EBS). Twin air compressor with heated dryer, exhaust brake and park brake control, spring brake cylinder on front and rear axle also.



CHASSIS SPECIFICATION

Issued
OCTOBER 2022

DAF LF260 FA 4x2 HYVA SKIP LOADER

Axles & Suspension:

Front Axle Type: 152N vertical offset at 100 mm. Parabolic leaf suspension with shock absorbers and stabiliser – Max Load: 7.5 ton

Single Reduction Rear Axle Type: SR1132 with asymmetric parabolic leaf suspension and shock absorbers – Max Load: 11.5 ton

Wheels & Tyres:

Steel disc wheel rims finished in silver grey with wheel protection rings and centre section also silver grey.

Front & Rear Axles:

- Tyre Size: 315/80R22.5
- Wheel Rim Size: 225 mm x 90 mm

Rear Axles:

- Tyres are premium make.
- On / Off road tread pattern fitted.

Electrical Power Supply:

Alternator 80 A (2 x 175 Ah batteries)

Rear light units LED

GVC & GCM:

Chassis weigh related technical GVM max. 19000 kg

Warranty:

1 year chassis cab with 2nd & 3rd year Driveline. This takes care of all warrantable repairs on the vehicle for the first two years and on the driveline for this year together with associated with breakdown coverage.

Service & Maintenance:

Two options are available at additional monthly cost:

Option 1) Compliance package.

Option 2) Full R&M Package, please ask for a full details or a monthly cost.

Please ask for full details and monthly costs.

Issued
OCTOBER 2022

DAF LF260 FA 4x2 HYVA SKIP LOADER



SKIP SPECIFICATION

Issued
OCTOBER 2022

DAF LF260 FA 4x2 HYVA SKIP LOADER

Body Description:

The HYVA 2012 XL skip loader platform is constructed from high tensile steel, incorporating two heavy duty wear strips each side of the bed along with fully adjustable skips stops to suit all types of containers both lengths and width.

The cab guard is sloped with bar viewing mesh. The independent or synchronised operational telescopic arms are powered by two high pressure main lifting rams which are covered with sliding aluminium guards. Certificated lifting chains with 2 hole steel key plates (SK1).

Additional Items:

Stabilizer jacks with articulated flat feet with side to side levelling ability

Rear access step and closed rear skirt with under-run

Control located on the O/s External emergency stop button 2

Double operated tipping hooks

The HYVA easy action sheeting system is also operated from the control unit on the O/S.

